


## 3193 male stud run tee, BSPP and M5 thread



plastic body complete  
with integral 'O' ring seal,  
nickel-plated brass stud



*the body is orientable for  
positioning purposes*

Ø D	C		E	F	G	H	H1	L	
4	M5x0,8	3193 04 19	3,5	8	8,5	26	11,5	14,5	0,004
4	G1/8	3193 04 10	5	13	8,5	23	8,5	14,5	0,008
4	G1/4	3193 04 13	5,5	16	8,5	23	8,5	14,5	0,013
6	M5x0,8	3193 06 19	3,5	8	10,5	29,5	12,5	17,5	0,007
6	G1/8	3193 06 10	5	13	10,5	27	10	17,5	0,010
6	G1/4	3193 06 13	5,5	16	10,5	27	10	17,5	0,015
8	G1/8	3193 08 10	4,5	13	13,5	36,5	14	23	0,017
8	G1/4	3193 08 13	5,5	16	13,5	34,5	12	23	0,020
8	G3/8	3193 08 17	5,5	20	13,5	34,5	12	23	0,023
10	G1/4	3193 10 13	5,5	16	16	42	15,5	26,5	0,021
10	G3/8	3193 10 17	5,5	20	16	40,5	14	26,5	0,023
10	G1/2	3193 10 21	7,5	24	16	40,5	14	26,5	0,039
12	G1/4	3193 12 13	5,5	16	19	48	17	31	0,087
12	G3/8	3193 12 17	5,5	20	19	46,5	15,5	31	0,088
12	G1/2	3193 12 21	7	24	19	46,5	15,5	31	0,091
14	G3/8	3193 14 17	5,5	20	22	56,5	21,5	35,5	0,110
14	G1/2	3193 14 21	7	24	22	51	16	35,5	0,120