



Rubber matting

Saturn Fine Rib BR

Quality:	NR/NBR
Colour:	Black, Gray
Temperature range:	-30° to +70°C
Specific gravity:	1,45 grs/cm ³
Hardness:	65 Shore A +/- 5
Tensile strength:	3,5 Mpa
Elongation at break:	250%

Features: Anti-slip ribbed surface on one side and a fine cloth impression pattern on the other side.

Application: Loose lay applications for floors, walkways, runners, loading areas, workbenches and general-purpose areas.

Thickness (mm)	Insertion(s) (no.)	Insertion type	Width (mtr)	Length (mtr)	Colour	Article nr.
3	0/1	cotton	1/1,2	10	Black	MR65 3/0
3	0	-	1/1,2/1,4	10	Grey	MR65G 3/0
4	0	-	1	10	Black	MR65 4/0



Rubber matting

Saturn Basic Fine ÜãÁÓÜÁ

Quality:	NBR
Colour:	Black
Temperature range:	-30° to +70°C
Specific gravity:	1,45 grs/cm ³
Hardness:	65 Shore A +/- 5
Tensile strength:	4,0 Mpa
Elongation at break:	200%

Features: Anti-slip ribbed surface on one side and a fine cloth impression pattern on the other side.

Application: Loose lay applications for floors, walkways, runners, loading areas, workbenches and general-purpose areas.

Thickness (mm)	Width (mtr)	Length (mtr)	Quality	Article nr.
2,7	1/1,2	10	NBR/SBR	MR65NBR 2,7/0