

YL-32



STANDARD DIE SETS

| Size | Range (mm) | Length |
|--------------|------------|--------|
| 32-10 | 10-13 | 55 |
| 32-13 | 13-16 | 55 |
| 32-16 | 16-19 | 55 |
| 32-19 | 19-22 | 55 |
| 32-22 | 22-26 | 55 |
| 32-26 | 26-30 | 55 |
| 32-30 | 30-34 | 75 |
| 32-34 | 34-39 | 75 |
| 32-39 | 39-45 | 75 |
| 32-45 | 45-52 | 90 |
| 32-52 | 52-57 | 90 |
| 32-57 | 57-64 | 90 |
| 32-64 | 64-69 | 100 |
| 32-69 | 69-79 | 100 |

TECHNICAL SPECIFICATIONS

| | |
|---|-------------------|
| Max hose size | 2" 4 SP |
| Crimping force (kN): | 2200 |
| Max crimping Ø (mm): | 79 |
| Max opening (mm): | die diameter + 32 |
| Standard motor: | 3,6 kW 400V 3-ph |
| Different voltage versions available | |
| Control | Digital control |
| Master dies opening / Length (mm): | 132/80 |
| Crimping range (mm): | 10 – 79 |
| Weight (kg) | 270 (without oil) |
| Dimensions (LxWxH mm) | 600 x 480 x 1300 |
| Die sets | Standard |
| 10-13-16-19-22-26-30-34-39-45-52-57-64-69 | |
| Quick Change-set | Standard |
| Foot pedal | Standard |
| Stand for machine | Standard |

WWW.DHYDRO.COM