

YL-125



TECHNICAL SPECIFICATIONS

Max hose size	6"
Crimping force (kN):	4000
Max crimping Ø (mm):	202
Max opening (mm):	die diameter + 125
Standard motor:	5,5kW 400V 3-Ph
Different voltage versions available	
Control	Digital control
Master dies opening / Length (mm):	335/116
Crimping range (mm):	10 - 202
Weight (kg)	3000 (without oil)

STANDARD DIE SETS

Size	Range (mm)	Lenght
32-10	10-13	55
32-13	13-16	55
32-16	16-19	55
32-19	19-22	55
32-22	22-26	55
32-26	26-30	55
32-30	30-34	75
32-34	34-39	75
32-39	39-45	75
32-45	45-52	90
32-52	52-57	90
32-57	57-64	90
32-64	64-69	100
32-69	69-74	100
32-74	74-78	110
32-78	78-87	110
125-84	84-92	116
125-92	92-100	116
125-100	100-108	116
125-108	108-116	116
125-116	116-126	116
125-126	126-136	116
125-136	136-146	116
125-146	146-156	116
125-156	156-166	116
125-166	166-178	116
125-178	178-190	116
125-190	190-202	116

Dimensions (LxWxH mm) 1050 x 1300 x 1750

Die sets Standard

10-13-16-19-22-26-30-34-39-45-52-57-64-69-74-78-84-92-100-108-116-126-136-146-156-166-178-190

Quick Change-set Standard

Back stop device Standard

Foot pedal Standard

WWW.DHYDRO.COM

Wahlforssinkatu 10 - 80100 Joensuu - Finland - Tel. +358 13 120 490 - info@dhydro.com