



OIL AND SIMILAR PRODUCTS - 150 bar

PAINTED STEEL

ATEX directive
IIB 2 GD c T4 T135 °C X



FIXED

| Article |
|-----------------|
| S. 330 8330.400 |
| S. 330 8330.402 |

| Article |
|-----------------|
| S. 390 8390.400 |
| S. 390 8390.401 |
| S. 390 8390.402 |

| Article |
|-----------------|
| S. 430 8430.400 |
| S. 430 8430.401 |
| S. 430 8430.402 |

| Article |
|-----------------|
| S. 530 8530.400 |
| S. 530 8530.401 |
| S. 530 8530.402 |

| Article |
|--------------------|
| S. 540 8540.400 |
| S. 540 8540.411 ** |
| S. 540 8540.412 ** |
| S. 540 8540.413 * |
| S. 540 8540.405 |
| S. 540 8540.406 |

| Article |
|-----------------|
| S. 560 8560.400 |

SWIVELLING



| Article |
|---------|
| - |

Supplied with:

- hoses in black synthetic rubber
- zinc plated steel couplings
- carbon steel swivel joint
- "polyurethane" seals



| Hose supplied | Connection | |
|----------------------|------------|--------------|
| | inlet | outlet |
| without hose | F1/2"G | F 3/8"-1/2"G |
| 12m - 3/8" (995.312) | F1/2"G | M1/2"G |

| without hose | F1/2"G | F 3/8"-1/2"G |
|----------------------|--------|--------------|
| 12m - 3/8" (995.312) | F1/2"G | M1/2"G |
| 17m - 3/8" (995.317) | F1/2"G | M1/2"G |

| without hose | F1/2"G | F1/2"G |
|----------------------|--------|--------|
| 10m - 1/2" (996.310) | F1/2"G | M1/2"G |
| 15m - 1/2" (996.315) | F1/2"G | M1/2"G |

for ABS hose reels Series 430 see page 152

| Article |
|----------|
| 8520.400 |
| 8520.401 |
| 8520.402 |

| without hose | F1/2"G | F1/2"G |
|----------------------|--------|--------|
| 20m - 1/2" (996.320) | F1/2"G | M1/2"G |
| 25m - 1/2" (996.325) | F1/2"G | M1/2"G |

| Article |
|-------------|
| 8550.400 |
| 8550.411 ** |
| 8550.412 ** |
| 8550.413 * |
| 8550.405 |
| 8550.406 |

| without hose | F1"G | F1"G |
|-----------------------|--------|--------|
| 15m - 3/4" (997.3315) | F1"G | M3/4"G |
| 20m - 3/4" (997.3320) | F1"G | M3/4"G |
| 15m - 1" (998.3315) | F1"G | M1"G |
| without hose | F1/2"G | F1/2"G |
| 30m - 1/2" (996.330) | F1/2"G | M1/2"G |

* 50 bar
** 100 bar

* 50 bar
** 100 bar

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reels.

The **template** supplied facilitates drilling of the holes and therefore hose reels fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reels installation and enables 55° rotation to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

