

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.
For example:
300/30/SO

FIXED PAINTED STEEL



P/N

FIXED S. STEEL AISI 304



P/N

Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- AISI 304 stainless steel swivel joint
- Viton® seals
- central shaft in galvanized steel or stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	P/N	Hose supplied	Connection	
				Inlet	Outlet
S. 300	300/30	302/30	without hose	F 3/8"G	F 3/8"G
	300/31	302/31	12m 5/16" (943/12)	F 3/8"G	F 3/8"G
S. 350	350/30	352/30	without hose	F 3/8"G	F 3/8"G
	350/31	352/31	12m 5/16" (943/12)	F 3/8"G	F 3/8"G
	350/32	352/32	17m 5/16" (943/17)	F 3/8"G	F 3/8"G
S. 430	430/30	434/30	without hose	F 3/8"G	F 1/2"G
	430/31	432/31	12m 3/8" (955/12)	F 3/8"G	F 3/8"G
	430/32	432/32	18m 3/8" (955/18)	F 3/8"G	F 3/8"G
S. 4430 ABS	4430/30	4434/30	without hose	F 3/8"G	F 1/2"G
	4430/31	4432/31	12m 3/8" (955/12)	F 3/8"G	F 3/8"G
	4430/32	4432/32	18m 3/8" (955/18)	F 3/8"G	F 3/8"G
S. 530	530/30	534/30	without hose	F 3/8"G	F 1/2"G
	530/31	532/31	25m 3/8" (955/25)	F 3/8"G	F 3/8"G
	530/32	532/32	20m 3/8" (955/20)	F 3/8"G	F 3/8"G
S. 540	540/30	544/30	without hose	F 3/8"G	F 1/2"G
	540/31	542/31	30m 3/8" (955/30)	F 3/8"G	F 3/8"G
S. 560	560/30	564/30	without hose	F 3/8"G	F 1/2"G
	560/31	562/31	40m 3/8" (955/40)	F 3/8"G	F 3/8"G
	560/32	562/32	50m 3/8" (955/50)	F 3/8"G	F 3/8"G

Rubber handles, mounted on hose terminal part, are available for all the above series. For more information look at page 50.



Atex 94/9

- II 3GD c X (only for series 300-350-4430 ABS)
- IIB 2GD c T4 T135°C X

USES

