



WATER MAX 130 °C - 100-200-400 bar

AISI 304 STAINLESS STEEL

Supplied with:

- AISI 304 stainless steel couplings
- AISI 304 stainless steel swivel joint
- "Viton®" seals (100-200 bar)
- "Teflon®" seals (400 bar)




ATEX directive
IIB 2 GD c T4 T135 °C X

FIXED



Article

SWIVELLING




Article

Connection

inlet

outlet

S. 430



Water 130 °C **100** bar

8434.200

8424.200

F1/2"G

F1/2"G

Water 130 °C **200** bar

8434.300

8424.300

F3/8"G

F1/2"G

Water 130 °C **400** bar

8434.350

8424.350

F3/8"G

F1/2"G

S. 530



Water 130 °C **100** bar

8534.200

8524.200

F1/2"G

F1/2"G

Water 130 °C **200** bar

8534.300

8524.300

F3/8"G

F1/2"G

Water 130 °C **400** bar

8534.350

8524.350

F3/8"G

F1/2"G

S. 540



Water 130 °C **100** bar

8544.200

8554.200

F1"G

F1"G

8544.205

8554.205

F1/2"G

F1/2"G

Water 130 °C **200** bar

8544.300

8554.300

F3/8"G

F1/2"G

Water 130 °C **400** bar

8544.350

8554.350

F3/8"G

F1/2"G

S. 560



Water 130 °C **100** bar

8564.200

-

F1"G

F1"G

8564.206

-

F1/2"G

F1/2"G

Water 130 °C **200** bar

8564.300

-

F3/8"G

F1/2"G

Water 130 °C **400** bar

8564.350

-

F3/8"G

F1/2"G

FIXED HOSE REELS INSTALLATION

The quick coupling support is equipped with 4 slot holes that allow an easy and safe installation of the hose reels.

The **template** supplied facilitates drilling of the holes and there fore hose reels fixing.

SWIVELLING HOSE REELS INSTALLATION

The **quick coupling swivelling support** facilitates hose reels installation and enables **55° rotation** to the right or left or locking in **fixed positioned at 0°** by means of clamping with two screws.

