



ART. 8524.200

AISI 304 and 316 stainless steel hose reels

Fixed hose reel in stainless steel AISI 304, s.530, for hot water, 100 bar, without hose. Inlet-outlet G 1/2" (f)



FLUIDS

ANTIFREEZE | WINDSHIELD FLUID | WATER | ADBLUE® | CLEANING DETERGENT

SECTORS

AGRICULTURE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Pressure	bar	100
Compatible fluids		water max 130 °C, oils and similar products
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		swivelling
Material		AISI 304 stainless steel
Couplings		-
Hose		-
Ø and hose length	Ø - m	-
Inlet		G 1/2" (f)
Outlet		G 1/2" (f)
Reel flow path		AISI 304 stainless steel
Internal drum width	mm	104

RAASM SpA


via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright ® 2020 All rights reserved to RAASM S.p.A.



Overall dimensions



RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.