



MANUFACTURING & MACHINE TOOLS

**Air and water**

Water discharge under pressure on industrial or urban sites and all water discharge applications in building and public works.

**Advantages**

- Extremely resistant to ageing and atmospheric conditions.
- Highly flexible and easy-to-hold due to the fluted cover.

**Technical description**

**Inner tube:** SBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** EPDM, green, fluted.

**Temperature range:** -30°C to +70°C.

**Standard/Approval:**

In compliance with ISO 1403 type 2 (except branding).

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock (●) or min. order m
12.7 ±0.6	4.0	20.7 ±0.7	10	30	70	0.28	20	0061511	□
							40	0061510	●
15.8 ±0.7	4.1	24.0 ±0.8	10	30	80	0.34	20	0061521	●
							40	0061520	●
							80	0061522	●
19.4 ±0.7	4.5	28.4 ±0.8	10	30	120	0.45	20	0061541	●
							40	0061540	●
							80	0061542	●
25.4 ±1.0	4.8	35.0 ±1.1	10	30	150	0.60	20	0061551	●
							40	0061550	●

□ Upon availability.

Tolerance on length: ±1% (ISO 1307 Standard).



Digital version

