

Smooth bore PTFE Liner with SS 304 braid with or without PVC covering



Braiding meets or exceeds ISO 7313/SAE AS620

All TRAX High performance brake hoses can be supplied with a clear PVC cover. A wide range of colour options are available, in solid and neon (transparent).

TRAX Brake-lines have been tested and certified in accordance with the stringent Federal Motor Vehicle Standard 106 SS (FMVS) all qualification criteria were successfully met or in most cases exceeded. All TRAX brake-lines are individually inspected and pressure tested prior to shipment.

Brake line kits are available from TRAX in any combination of coloured covered Teflon hose and fittings of your material choice. Just provide the Make, Model and Year of your bike and leave the rest to us.



Size	PTFE Wall thickness	1 / Đ (Nom.)	0 / 0 no cover	0 / 0 incl cover	Bend Radius	Working Pressure	Burst Pressure	Product Reference
Dash 3	0,91 mm	3.5 mm	6.27 mm	na	38 mm	321 bar	966 bar	T1003
Dash 4	0,72 mm	5,3 mm	8,40 mm	88	51 mm	276 bar	828 bar	T1D04
Dash 5	0,76 mm	6,5 mm	8.95 mm	53	70 mm	205 bar	615 bar	T1D05
Dash 6	0,76 mm	7,9 mm	11,10 mm	na	100 mm	230 bar	690 bar	T1006
Dash 8	0,76 mm	10,5 mm	13,40 mm	na	133 mm	195 bar	586 bar	T1D08
Dash 10	0,76 mm	12,9 mm	16,20 mm	88	178 mm	161 bar	483 bar	T1D10
Including Clear	PVC cover							
Size	PTFE Wall thicknes	(VD (Nom.)	0 / D no cover	0 / 0 incl cover	Bend Radius	Working Pressure	Burst Pressure	Product Reference
Dash 3	0,91 mm	3,5 mm	6,27 mm	7,27 mm	38 mm	321 bar	966 bar	T10PCLR03
Dash 4	0,72 mm	5,3 mm	8,40 mm	9,40 mm	51 mm	276 bar	828 tiar	T10PCLR04
Dash 5	0,76 mm	6,5 mm	8.95 mm	9,95 mm	70 mm	205 bar	615 bar	T10PCLR05

Private label Branding? Go on ... make a name for yourself.

