

OIL & PETROLEUM DISPENSING/FUELING

SOFTWALL PETROL HOSE EN 1360



APPLICATION: A premium quality textile braid rubber hose for use on all types of fuel dispenser handling petroleum and diesel fuels.

CONSTRUCTION:
Tube: Black Chemigum® (Nitrile) synthetic rubber (ORS) with excellent resistance to diesel oils, reformulated petrol and alcohol blends.
Reinforcement: Textile braid with antistatic bonding wires
Cover: Black, static conducting, ozone resistant synthetic rubber

TEMPERATURE: -30°C/+55°C (-22°F/+131°F)

BRANDING: »SOFTWALL PETROL HOSE by GOODYEAR, Made in EU., Goodyear EN 1360:2005 Type 1 Ω, ID mm, 16 bar«.

COUPLINGS: Goodyear specification mild steel plated or chromed brass.

STANDARDS: ISO 1307
EN 1360

ID		OD	WP		BR	W	SL
mm	inch	mm	bar	psi	mm	g/m	m
15,9	5/8	25,4	16	232	160	290	100
19,1	3/4	29,0	16	232	190	320	100
25,4	1	35,0	16	232	255	440	50

Hose safety factor (burst pressure) 4:1.

Air & Water

Air Heavy Duty

Water

Multi-purpose

Oil & Petroleum
Transfer
Dock
Dispensing/Fueling

Chemical

Food

Cleaning & Washdown

Marine

Material Handling

Steam

Welding

Appendix
Additional Products
Chemical Charts
General Information



Information is valid throughout 2008. Due to continual product improvements, Veyance Technologies, Europe reserves the right to alter specifications without prior notice. For the most current product information please contact your local Veyance Technologies, Europe. Sales/Marketing office.