



**ESPIROFLEX**  
FABRICA DE TUBERIA FLEXIBLE

## TRANSLIQUID S AZURO

### CHARACTERISTICS

Tube made by co-extrusion of vinyl components, according to the Quality Norm ISO 3994. Non toxic and food quality according to the European regulations EC 1935/2004 and EU 10/2011. Reinforced by a rigid PVC spiral practically non deformable and anti choke, in blue colour, which provides the tube with a great consistence. The spiral is covered by a transparent, flexible material with food quality, with a smooth external surface.

The tube is smooth inside which prevents the accumulation of sediments and ease the cleaning of them.

Withstand the environmental agents and also several chemical products

Temperature range between  $-10^{\circ}\text{C}$  y  $60^{\circ}\text{C}$ .

### APPLICATIONS

Pumping of alcoholic liquids (up to  $20^{\circ}$ ), alimentary liquids which require simulants A, B and C under OM2 conditions according to the regulation EU 10/2011.

Pumping and aspiration in agriculture watering

### TECHNICAL DATA

$\varnothing$ INT. mm	WALL mm	WEIGHT g/m	VACUUM m H <sub>2</sub> O	SERVICE PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm
32	3.0	350	7	4	12	95
38	3.2	480	7	4	12	115

Pressures at room temperature at laboratory

13-07-2020