

# Codan 3320 Air / Water Hose



## Codan 3320 - EN ISO 8031: 1997

Black, flexible universal hose for air and water. Available with either blue or red stripes. Electrically conductive liner prevent the build-up of static electricity;  $R < 10^6 \Omega$  in accordance with EN ISO 8031: 1997. High-quality EPDM inside and outside ensures good weather and ozone resistance in any environment. For use in industrial applications for cold and hot water, compressed air and chemicals (acids excepted). Resistant to acetates and ketones. Please contact Codan for further information.

**Type nr.** 3320

**Application:** Air / Water Hose

**Standard Length:** 50 metres

**Working Temperature:** -40°C to 95°C

**Inside:** EPDM

**Colour:** Black

**Reinforcement:** PVA

**Outside:** EPDM

**Colour:** Black

**Standards:** EN ISO 8031: 1997

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
6,0	13,0	20	60	40	150	3320006000
8,0	15,0	20	60	50	180	3320008000
10,0	17,0	20	60	60	210	3320010000
13,0	21,0	20	60	80	300	3320013000
16,0	24,0	20	60	100	350	3320016000
19,0	28,0	20	60	115	470	3320019000
25,0	35,0	20	60	150	670	3320025000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Fax +45 56 64 65 48  
Mail: [info@codan.com](mailto:info@codan.com) [www.codan.com](http://www.codan.com)

04/12/2017