



# EPDM rubber sheet

## Manticore Medium

<b>Quality:</b>	EPDM/SBR
<b>Colour:</b>	Black
<b>Temperature range:</b>	-30° to +90°C
<b>Specific gravity:</b>	1,35 grs/cm <sup>3</sup>
<b>Hardness:</b>	65 Shore A +/- 5
<b>Tensile strength:</b>	6 Mpa
<b>Elongation at break:</b>	250%

**Features:** Widely used weather and cold resistant industrial rubber quality with good mechanical properties and chemical resistance. Suitable for open air and good ozone resistance.

**Application:** Automotive industry, outdoor use and solar panels.

Thickness (mm)	Width (mtr)	Length (mtr)	Article nr.
1	1,4	20	EP65130 1/0
1,5	1,4	15	EP65130 1,5/0
2	1,4	10	EP65130 2/0
3	1,4	10	EP65130 3/0
4	1,4	10	EP65130 4/0
5	1,4	10	EP65130 5/0
6	1,4	10	EP65130 6/0
8	1,4	5	EP65130 8/0
10	1,4	5	EP65130 10/0



**Rubber Europe**

Thickness Tolerances		
Over (mm)	Upto (mm)	Tolerance +/- (mm)
0.5	2	0.2
2	3	0.3
3	6	0.4
6	10	0.5
10	15	0.8
15	25	1.0

Roll length Tolerances	
Length (mm)	Tolerance +/- (mm)
1.000	50
5.000	250
10.000	500
20.000	1.000

Roll width Tolerances	
length (mm)	Tolerance +/- (mm)
900	18
1.000	20
1.220	24
1.300	26
1.400	28