



EPDM rubber sheet

Manticore Premium

Quality:	EPDM
Colour:	Black
Temperature range:	-40° to +130°C
Specific gravity:	1,25 grs/cm ³
Hardness:	65 Shore A +/- 5
Tensile strength:	8 Mpa
Elongation at break:	350%

Features: Excellent weather and cold resistant industrial rubber quality with good mechanical properties and chemical resistance. Suitable for open air and good ozone resistance.

Application: Automotive industry, hot water seals, outdoor use and solar panels.

Thickness (mm)	Width (mtr)	Length (mtr)	Article nr.
1	1,4	20	EP65120 1/0
2	1,4	10	EP65120 2/0
3	1,4	10	EP65120 3/0
4	1,4	10	EP65120 4/0
5	1,4	10	EP65120 5/0
6	1,4	10	EP65120 6/0
8	1,4	5	EP65120 8/0
10	1,4	5	EP65120 10/0



Rubber Europe

Thickness Tolerances		
Over (mm)	Upto (mm)	Tolerance +/- (mm)
0.5	2	0.2
2	3	0.3
3	6	0.4
6	10	0.5
10	15	0.8
15	25	1.0

Roll length Tolerances	
Length (mm)	Tolerance +/- (mm)
1.000	50
5.000	250
10.000	500
20.000	1.000

Roll width Tolerances	
length (mm)	Tolerance +/- (mm)
900	18
1.000	20
1.220	24
1.300	26
1.400	28